




Series  
ADPS

# Differential Pressure Switch

With Adjustable Setting

CE



The **Series ADPS Adjustable Differential Pressure Switch** is designed for pressure, vacuum, and differential pressures. The scaled adjustment knob allows changes to the switching pressure to be made without a pressure gage. The ADPS is available with settings from 0.08" w.c. (20 Pa) up to 16" w.c. (4000 Pa). The silicone diaphragm and PA 6.6 body make the series ADPS perfect for use with air and other noncombustible gases.

## Typical Applications Include:

- Monitoring air filters and ventilators.
- Monitoring industrial cooling-air circuits.
- Overheating protection for fan heaters.
- Monitoring flows in ventilation ducts.
- Controlling air and fire-protection dampers.
- Frost protection for heat exchanges.

Model No.	Range	Price
<b>Standard Version</b>		
ADPS-01-2-N	.08 to .80" WC (20-200Pa)	\$21.00
ADPS-04-2-N	.12 to 1.60" WC (30-400Pa)	21.00
ADPS-03-2-N	.20 to 2.00" WC (50-500Pa)	21.00
ADPS-05-2-N	.80 to 4.00" WC (200-1000Pa)	21.00
ADPS-06-2-N	2.00 to 10.00" WC (500-2500Pa)	21.00
ADPS-07-2-N	4.00 to 16.00" WC (1000-4000Pa)	21.00

## SPECIFICATIONS

**Service:** Air and noncombustible, compatible gases.

**Wetted Materials:** Diaphragm Material: Silicone. Housing Material: switch body: PA 6.6; Cover: Polystyrene.

**Temperature Limits:** Process ambient temperature from -4 to 185°F (-20 to 85°C).

**Pressure Limits:** Max. Operating Pressure: 40" W.C. (10 kPa) for all pressure ranges.

**Switch Type:** Single-pole double-throw (SPDT).

**Repeatability:** ±15% FS.

**Electrical Rating:** Standard: Max., 1.5A/250 VAC, max. switching rate: 6 cycles/min.; Gold Contact Option: 0.4 A/250 VAC.

**Electrical Connections:** Push-on screw terminals. M20x1.5 with cable strain relief or optional 1/2" NPT connection.

**Process Connections:** 5/16" (7.94 mm) outside diameter tubing, 1/4" (6.0 mm) inside diameter tubing.

**Mounting Orientation:** Vertically, with pressure connections pointing downwards.

**Mechanical Working Life:** Over 10<sup>6</sup> switching operations.

**Weight:** 5.6 oz (160 g).

**Enclosure Rating:** NEMA 13, IP54.

**Agency Approvals:** CE.